

	DISCO <sup>1</sup>	3600 FRC	3600 FC	3600 F	3200 FRC	3200 FC	3200 F	3150 F	4000	3600 RC	3600 / 3600 C	3200 RC	3200 / 3200 C	2800 RC	2800 / 2800 C	3550	3150 C	3150	2750 RC	2750 C	2750	290	250	210 RC	210	3600 TRC	3600 TC	3200 TRC	3200 TC	3200 TC	AUTOSWATHER	3150 TRC	3150 TC	3150 TC	3150 TC	FLAPTRAPPER		
		Front mowers							CONTOUR rear mowers							Side-mounted rear mowers										Trailed mowers												
<b>Dimensions and weights</b>																																						
Working width	m	3.40	3.40	3.40	3.00	3.00	3.00	3.00	3.80	3.40	3.40	3.00	3.00	2.60	2.60	3.40	3.00	3.00	2.60	2.60	2.60	2.85	2.45	2.10	2.10	3.40	3.40	3.00	3.00	3.00	3.00	3.00	3.00	3.00	3.00			
Hitch category		II	II	II	II	II	II	II	III	III	II / III	III	II / III	II	II	II	II	II	II	II	II	II	II	II	II	II	II	II	II	II	II	II	II	II	II			
PTO shaft speed	rpm	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850) / 540 (460)	1000 (850) / 540 (460)	1000 (850) / 540 (460)	540 (460)	540 (460)	540 (460)	540	540	540	540	1000 (850) / 850	1000 (850) / 850	1000 (850) / 850	1000 (850) / 850	1000 (850) / 850	1000 (850) / 850	1000 (850) / 540 (460)	1000 (850) / 540 (460)	1000 (850) / 540 (460)	1000 (850) / 540 (460)			
Transport width	m	3.40	3.40	3.40	3.00	3.00	3.00	3.00	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	3.40	3.40	3.00	3.00	3.00	3.00	3.00	3.00	3.00	3.00			
Machine height	m	–	–	–	–	–	–	–	3.90	3.57	3.57	3.19	3.19	2.86	2.86	3.87	3.70	3.70	3.29	3.29	3.29	3.40	3.00	2.65	2.65	–	–	–	–	–	–	–	–	–	–			
Weight (according to conditioner)	approx. kg	1220	1195	870	1040	1010	775	685	1040	1300	950 / 1280	1180	870 / 1150	1070	810 / 1050	845	1130	785	1060	1040	725	630	600	880	560	2380	2320	2300	2230	2430	1900	1750	1900	1900	1900			
<b>Mower</b>																																						
MAX CUT mower bar <sup>2</sup>		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	–	–	–	–	●	●	●	●	●	●	●	●	●	●			
ACTIVE FLOAT suspension		○ <sup>3</sup>	○ <sup>3</sup>	○ <sup>3</sup>	○ <sup>3</sup>	○ <sup>3</sup>	○ <sup>3</sup>	○ <sup>3</sup>	●	●	●	●	●	●	●	–	–	–	–	–	–	–	–	–	–	●	●	●	●	●	●	–	–	–	–			
Discs (2 knives per disc)		8	8	8	7	7	7	7	9	8	8	7	7	6	6	8	7	7	6	6	6	7	6	5	5	8	8	7	7	7	7	7	7	7	7			
Quick blade change		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	–	–	–	–	●	●	●	●	●	●	●	●	●	●			
<b>Conditioner</b>																																						
Conditioner speed	rpm	950	900 / 770	–	950	900 / 770	–	–	–	940	– / 910	940	– / 910	940	– / 910	–	900	–	900	900	–	–	–	940	–	1050	1080 / 900	1050	1080 / 900	1200	1033	900 / 770	1033	1033	1033			
<b>Hydraulics</b>																																						
Hydraulic spool valves		(1 da <sup>4</sup> + 1 sa <sup>3</sup> )							(1 sa <sup>3</sup> )	1 x da <sup>5</sup> (+ 1 x sa)							1 x sa										1 x sa + 1 x da (+ 1 x sa)					2 x sa + 1 x da (+ 1 x sa)		1 x sa + 1 x da				
<b>Equipment</b>																																						
Hydraulically foldable protective side covers		○	○	○	○	○	○	–	○	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–			
Wide crop spreader		–	–	–	–	–	–	–	–	–	–/○	–	–/○	–	–/○	–	○	–	–	○	–	–	–	–	–	–	○	–	○	○	–	○	–	○	–			
Adjustable swathing plates		●	●	–	●	●	–	–	–	●	–/●	●	–/●	●	–/●	–	●	–	●	●	–	–	–	●	–	●	●	●	●	●	●	●	●	●	●			
Outside swathing disc		–	–	● (2 x)	–	–	● (1 x)	● (1 x)	○	–	○/–	–	○/–	–	○/–	○	–	○	–	–	○	–	–	–	–	–	–	–	–	–	–	–	–	–	–			
High-cut skids		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○			
Twin high-cut skids		○	○	○	○	○	○	○	○	○	○	○	○	○	○	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–			
Wear skids		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○			
Bar protection device (for intensive use conditions)		○	○	○	○	○	○	–	–	○	–/○	○	–/○	○	–/○	–	–	–	–	–	–	–	–	–	–	○	○	○	○	○	○	–	–	–	–			
Warning signs with lighting		○ <sup>6</sup>	○ <sup>6</sup>	○ <sup>6</sup>	○ <sup>6</sup>	○ <sup>6</sup>	○ <sup>6</sup>	○	○	○	○	○	○	○	○	○	○	○	○	○	○	–	–	–	–	●	●	●	●	●	●	●	●	●	●			
Hydraulic transport locking device		–	–	–	–	–	–	–	○	○	○	○	○	○	○	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–			
Mechanical breakback protection		–	–	–	–	–	–	–	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	–	–	–	–	–	–	–	–	–	–			

<sup>1</sup> C = tine conditioner, RC = roller conditioner, no suffix = without conditioner  
<sup>2</sup> Standard cut height 40 mm (infinitely variable adjustment 30–70 mm)  
<sup>3</sup> 1 x sa required for ACTIVE FLOAT option  
<sup>4</sup> 1 x da required for hydraulic protective cover folding option  
<sup>5</sup> With float position  
<sup>6</sup> Folding

CLAAS continually develops its products to meet customer requirements. This means that all products are subject to change without notice. All descriptions and specifications in this brochure should be considered approximate and may include optional equipment that is not part of the standard specifications. This brochure is designed for worldwide use. Please refer to your nearest CLAAS dealer and their price list for local specification details. Some protective panels may have been removed to present the function more clearly in photographs. To avoid any risks, you should never remove these protective panels yourself. In this context, please refer to the relevant instructions in the operator's manual.